

3000 NET by Alkenz

Alkenz SunShadow® Solar Screen fabrics offer a stylish and modern aesthetic for window treatments that minimize the negative effects of the sun, while preserving outward visibility.

3000 NET is the most widely used screen due to its 2x2 lightweight basket weave which offers ease of fabrication and versatility.

FEATURES

- A unique manufacturing process delivers technically superior fabrics that are backed by a limited lifetime warranty.
- Environmentally friendly and safe
- Flame Retardant
- Available in four openness factors 1%, 3%, 5%, 10%
- Available in 13 colors
- Versatile can be used in roller shades and panel track applications



The most widely used screen comes in 4 openness factors to suit any room.

Colors



WHITE/WHITE




BEIGE/GRAY






CHARCOAL/CHARCOAL













BRONZE/BRONZE



BEIGE/BEIGE



GRAY/BLUE GRAY



CHARCOAL/BRONZE

SPECIFICATIONS	3000 NET 1%	3000 NET 3%	3000 NET 5%	3000 NET 10%
Composition	25% Polyester, 75% PVC	25% Polyester, 75% PVC	25% Polyester, 75% PVC	25% Polyester, 75% PVC
Weight	15.28 oz/yd2 (518 g/m2)	13.12 oz/yd2 (445 g/m2)	12.39 oz/yd2 (420 g/m2)	11.36 oz/yd2 (385 g/m2)
Thickness	0.026 in (.66mm)	0.022 in (.55mm)	0.022 in (.55mm)	0.020 in (.50mm)
Width	78.7" (2m), 98.4" (2.5m), 118" (3m)	78.7" (2m), 98.4" (2.5m), 118" (3m)	78.7" (2m), 98.4" (2.5m), 118" (3m)	78.7" (2m), 98.4" (2.5m), 118" (3m)
Average roll length	33 yd (30m)	33 yd (30m)	33 yd (30m)	33 yd (30m)
Fire Classification	NFPA 701, M1, B2, B1	NFPA 701, M1, B2, B1	NFPA 701, M1, B2, B1	NFPA 701, M1, B2, B1
Environmental standards	Oeko-Tex Standard 100, ISO 14001, ISO 9001, Greenguard	Oeko-Tex Standard 100, ISO 14001, ISO 9001, Greenguard	Oeko-Tex Standard 100, ISO 14001, ISO 9001, Greenguard	Oeko-Tex Standard 100, ISC 14001, ISO 9001, Greengua

^{*}For complete technical information, current test results, performance specifications, and samples, please contact our marketing deparment.











