GUARDIAN Blackout



Azar Decorating Inc. 845-783-4198

FABRIC TECHNICAL **SPECIFICATIONS**

FABRIC COMPOSITION: 3 Ply (62.1% Vinyl, 31.6% Fiberglass,

6.2% Proprietary Coating)

BREAKING STRENGTH: 299 Warp Direction 299

Fill Direction

THICKNESS: 13.1 mil.

UV OPACITY: 100% Blackout

FABRIC THREAD COUNT: 59 threads per sq/in. (23 per sq/cm)

USAGE: Roller Shade Fabrics

FLAME RESISTANCE: NFPA No. 701—2019 Test Method 1

CERTIFICATIONS:

ASTM D3335-85a—Lead Testing
ASTM Method G-21-15—Resistance to Fungi

FABRIC WEIGHT: 12.8 oz/sq-yd (436.7 g/sq met)

WASHABILITY: Dust with a damp cloth. Scrub with warm water, mild detergent, and gentle rubbing.

FABRIC WARRANTY: Guardian blackout fabric is guaranteed to be free of any

manufacturing defects for period of 5 years.





PRODUCT FEATURES

Decorative woven look and feel.

Incredibly durable and stable.

Ability to withstand high heat and direct light. Will not crack, yellow, or develop pin-holes.

Great for commercial, institutional, hospitality, and residential applications.

Custom colors available for contract orders. Minimum production runs will apply

Azar Decorating Inc.

48 Bakertown Rd. Suite #404, Monroe NY 10950 P: 845-783-4198 | F: 845-783-8084 sales@azardecorating.com